

ST-S311NC



Feature:

- Single Channel Passive Video Transceiver
- Support HD Camera up to 8MP Solution
- Up to 1500M with any Active UTP Video Receiver
- PAL/NTSC Sign Real-time Video Transmission
- Exceptional Interference Rejection and Built-in Protection Setting
- Convenient Wiring Installation, Higher Cable Utilization Rate and Lower Composite Wiring Cost
- Compact Size; Tool-less install in seconds

Specification:

Maximum distance for HD720 Camera	350M
Maximum distance for HD1080 Camera	300M
Maximum distance for HD5/8MP Camera	200-180M
Coaxial Cable in/out Socket port	Male BNC, Female BNC, F head (optional)
Twisted-Pair Cable in/out socket port	Push Pin Terminals
Coaxial Cable in/out impedance	75Ω
Twisted-Pair cable in/out impedance	100Ω
Video CMRR/ Attenuation	60dB/ 0.3dB Typ
Wire Type	UTP CAT5,24-16AWG
Working temp. / relative humidity	-10°C to +55°C / <95%
Weight(Net)	50g/Pair

Package contains:

- ✓ Video Balun × 1Pair

Design and specifications are subject to change without notice

Website: www.styco.cn

Email: sales@styco.cn

Tel: +86 755 2221 3765

Fax: +86 755 2231 0765